Sangoma s300 VoIP Phone

Full Featured and Cost Effective

Designed to work with and PBXact, Sangoma IP phones are so smart you can quickly and eaily ust them right out of the box.

The Sangoma s300 is a full feature set phone with a competitive entry-level price point. The s300 IP phone can automatically locate PBXact to quickly and easily get full configuration right out of the box - true Zero Touch Configuration.

The s300 features industry standard Power over Ethernet, so no power cable or outlets required. It has full duplex speakerphone, dual Ethernet ports, five-way conference calling, high definition voice quality, and built in Virtual Private Network (VPN) capability.

"Finally a phone anyone in your office (or remote) can install, provision and start using just by plugging it into the network, and with Market Leading Security Features."

Quick Facts

- Market Leading Security Measures
- >> Full Duplex Speaker Phone
- Backlit LCD Display
- 5-way Conferencing
- Dual 10/100 Mbps Ethernet Ports
- » Optional Annual Support & Software Maintenance Plans

Buy a Bundle

Stop trying to piece together a new VoIP telephone system. With Sangoma's family of IP phones and industry expertise, everything your business needs for IP and Unified Communications can be ordered from a single vendor. Get the complete Sangoma solution all in one bundle:

- » Private Branch Exchange (PBX)
- Sateways
- » IP Phones



ADVANCED CAPABILITIES

Zero Touch Provisioning

VoIP telephones can be complex to install, and manually configuring many different parameters and hundreds of extensions can take hours. When you buy and install your Sangoma IP phones, the redirection server automatically points the phone to the Sangoma PBXact for configuration.



Other vendors have redirection servers, but they have to be programmed with details of the IP PBX. Only Sangoma can provide Zero Touch provisioning with PBXact.

EndPoint Manager Included

When using a Sangoma phone, EndPoint Manager software inside PBXact is automatically enabled. This lets your users control global settings, program their phone keys, map extensions, upload images, download new firmware, and much more.



Hot-Desking

For users without a permanent work desk, log in to any phone with your extension and password, and all your settings follow you instantly.

Perfect for call-center agents, and other roaming workers. It's as if you never left your desk at all!

Security with Built-in VPN

All Sangoma phones are pre-provisioned with a VPN client to automatically connect to the corporate PBXact Phone system. Perfect for remote workers to be able to access all their tools from the office without compromising security.

FEATURE SPECIFICATIONS

Phone Features:

- » Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- » Redial, call return, auto answer
- >> 5-way conferencing

IP-PBX Features:

- Busy Lamp Field (BLF)
- » Call park, call pickup
- » Music on hold
- » Voicemail

Voice Codecs Features:

- » HD voice
 - > HD handset
 - > HD speaker
- Codecs
 - iLBCG.722
 - > G.711(A/μ)
 - > GSM FR
 - > G.723
 - > G.729AB
 - > G.726 -32
- » Full-duplex hands-free speakerphone with AEC (Acoustic Echo Cancellation)

Display and Indicator:

- 3 132 x 48 pixel graphical LCD with backlight
- LED for call and message waiting indication
- >> Illuminated LEDs for line status information

Feature Keys:

- » 6 feature keys
 - > Headset
 - > Speaker
 - > Hold
 - > Mute
 - > Transfer
 - > Conference

- » Direct IP call
- Custom ring tones / provisioning
- Set date time automatically or manually
- » Dial plan per account
- » RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- » Action URL/URI
- Anonymous call, anonymous call rejection
- » Message Waiting Indicator
- > Intercom, paging
- Voice Activity Detection (VAD)
- » Auto Gain Control (AGC)
- Comfort Noise Generation (CNG)
- Acoustic Echo Cancellation (AEC)
- » Packet Loss Concealment (PLC)
- » Adaptive Jitter Buffer (AJB)
- » DTMF
 - > In-band
 - > RFC 2833
 - > SIP INFO
- Intuitive user interface with icons and soft keys
- » National language selection
- Caller ID with name and number
- 2 line keys with LED
- >> 4 context-sensitive "soft" keys
- » 6 navigation keys
- > Volume control keys

Interface:

- Dual-port 10/100 Mbps Ethernet
- » 1x RJ9 (4P4C) handset port

Management:

- Configuration
 - > Browser / LCD-Menu /
 auto-provision
 - > HD Speaker
- Auto-Provision via HTTP / HTTPS, FTP / TFTP
- » Auto-Provision with Pnp

- » Power over Ethernet (IEEE 802.3af) (PoE), class 3
- » Reset to factory, restart, reboot
- >> Local tracing log export, system log
- » Phone lock for personal privacy protection

> 802.1p/Q tagging (VLAN)

> Layer 3 ToS DSCP

» HTTPS certificate manager

» TLS (Transport Layer

AES encryption for

configuration file

» Digest authentication

using MD5/MD5-sess

» IPV4 / IPV6

Security)

» Open VPN

> Oos

≫ SRTP

Network and Security:

>> SIP v1, v2

Need more SIP Trunk info? Please visit



www.MyTelPros.com

- SIP server / proxy redundancy
- » NAT Traversal
 - > STUN mode
- » DHCP / static / PPPoE
- >> HTTP / HTTPS web server
- Time and date synchronization by SNTP
- DNS-NAPTR/DNS- SRV (RFC 3263)
- » IEEE802.1X

Languages:

- English
- >> French
- » German
- » Spanish
- » Portuguese
- » Russian
- > Italian
- » Polish

- > Turkish
- » Serbian
- > Chinese Simplified
- Chinese Traditional
- » Slovenian
- » Farsi
- » Slovak
- » Czech
- **Physical Features:**
- Shipping dimensions205mm (W) x 194mm(D) x 105mm (H)
- Shipping weight
 - > .91kg (2lbs)
- External power adapter *Sold separately (US, UK EUR versions)
- » Wall mountable

- » Power consumption (PSU)
 - > 1.6~2.6W
- Power consumption (PoE)
- > 2.0~3.2W > Operating humidity
- > 10~95%
- Operating temperature
 - > -10~50°C

